



VIDEO INTERCOM

Villa / Apartment Solutions



VIDEO INTERCOM



Doorway security monitoring



Multiple door opening modes, such as swiping card, password, etc.



One-button calling indoor station



Door opening by indoor station or mobile APP



Anti-tampering alarm, unlocked door alarm, etc.



Two-way talk communication between indoor station and video intercom



2.4G WiFi



Main features:

- ⊙ Classic Tones
- ⊙ A variety of mounting options, easy to install
- ⊙ Adjustable volume and ring tone
- ⊙ Low battery reminder



Chime

| Model | PAR-P2DOORCHI |
|---------------------|--|
| | |
| Audio | Built-in speaker |
| Set Button | Pairing setting and ringtone selection |
| Volume Button | Yes |
| RF433 | Yes |
| WiFi | No |
| Indicator | Built-in indicator |
| Working Environment | -20°C~50°C, Humidity: less than 95% |
| Dimensions(mm) | Ø73x32 |

Main features:

- ⊙ 2MP (1920X1080)
- ⊙ Wide field of view achieving doorway security monitoring
- ⊙ Access control function
- ⊙ Noise suppression and echo cancellation
- ⊙ Visual intercom function: two-way remote communication between the doorbell /mobile APP
- ⊙ Support door opening by swiping card or mobile APP
- ⊙ Support IR and white LED lights
- ⊙ Support tampering alarm and door contact alarm
- ⊙ Intelligent Analysis: video exception detection, face detection, face capture, etc.



Video Doorbell

| Model | PAR-P2DOORBELL |
|-----------------------|--|
| | |
| Image Sensor | 1/2.8" Progressive Scan CMOS |
| Lens | 2.3mm @F2.2 |
| MIN. Illumination | 0 lux (white LED ON) |
| Card Reading Duration | <1s |
| Card Number Storage | Max.3,000 |
| Audio | Built-in MICx1, built-in speakerx1 |
| RS485 | Yes |
| Alarm | 1CH alarm input |
| Other | 1CH Door Lock Output, 1CH Exit Button, 1CH Door Contact Input, 1CH Anti-Tamper Interface, Reset Button |
| Storage | 1CH built-in micro SD card slot, up to 256GB |
| Wiegand Interface | Yes |
| WiFi | Supports 2.4G WiFi function |
| Doorbell Button | Yes |
| Indicator | Yes |
| Ingress Protection | IP65 |
| Face Detection | Pupil distance of a facial image over 20 pixel can be detected |
| Power | DC12V/0.5A |
| PoE Power Supply | Yes |
| Working Environment | -20°C~50°C, Humidity: less than 95% |
| Dimensions(mm) | 150x50x29.8 |

Main features:

- ⊙ 3.5 inch TFT screen, 2MP (1920×1080)
- ⊙ Face recognition distance: 0.3m-2m
- ⊙ Support face detection technology distinguishing real faces from non-real face spoof attacks
- ⊙ Support multiple door opening modes (by swiping card, by password, by face recognition, etc.)
- ⊙ Support door opening by indoor station or by mobile APP
- ⊙ Support copy-prevention for IC card; support IC card encryption
- ⊙ Support anti-tampering alarm, One-button calling indoor station
- ⊙ Intelligent analytics: video exception detection, face detection, face capture, face comparison



Video Intercom Door Station

| Model | PAR-P2INTERCOM |
|-----------------------|--|
| |  |
| Image Sensor | 1/2.8" Progressive Scan CMOS |
| Card Reading Duration | <1s |
| Card Capacity | 10000 |
| Audio | Built-in MICx1, built-in speakerx1 |
| Storage | 1CH built-in micro SD card, up to 256GB |
| Reset / RS485 | Yes |
| Wiegand Interface | Yes |
| Alarm | 2CH alarm input; 1CH alarm output |
| Other | 2CH Door Lock Output, 2CH Door Contact Input, 2CH Exit Button, 1CH Anti-Tamper Interface |
| Swiping Card Area | Support IC card/EM card |
| Digital Buttons | Yes |
| Wi-Fi | Support 2.4G Wi-Fi function |
| PoE / P2P | Yes |
| Protection Grade | IP67, IK04 |
| Power | DC12V/PoE |
| Working Environment | -20 ~60 , Humidity: less than 95% |
| Dimensions(mm) | 210x104x30 |

Main features:

- ⊙ 7 inch IPS touch screen
- ⊙ A maximum of 6 indoor stations can be installed in the same room
- ⊙ Supports live preview of door stations and linked cameras
- ⊙ Supports snapshot when calling via door station (micro SD card required)
- ⊙ Supports "Do Not Disturb" function
- ⊙ Supports noise suppression and echo cancellation
- ⊙ 8CH zone alarm access function
- ⊙ Self-define unlocking password



Video Intercom Indoor Station

| Model | PAR-7DOORSTATION |
|--------------------------|---|
| |  |
| Operating System | Linux |
| Display Resolution | 1024X600, brightness: 300 cd/m2 |
| Operation Method | Capacitive touch screen |
| Video Input | Max. 4CH videos can be viewed simultaneously |
| Audio | Built-in speaker and microphone |
| Linked IPC | Max. 16CH |
| Linked Indoor Extensions | Max. 5 |
| Storage | Built-in micro SD card slot, up to 256GB |
| Reset | Yes |
| Alarm Input | 8CH |
| Wi-Fi | Yes, 2.4G Wi-Fi |
| Unlocking Button | Yes |
| RS485 | Reserved |
| Power | DC12V/POE |
| Working Environment | -20°C~50°C, Humidity: less than 95% |
| Dimensions(mm) | 180.6x135.6x26.8 |



