



ELEV-C5DRXIRA27135N

5 Megapixel HD Analog Outdoor Dome,
Motorized Varifocal, Up to 98' IR Range, D-WDR, DC12V

Features

- 5 Megapixel Resolution
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Motorized Varifocal 2.7-13.5mm
- True Day/Night with IR Range up to 98'
- D-WDR
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Withstand up to -40° F Operation
- IK10 Vandal Resistant
- 2D/3D DNR (Digital Noise Reduction)
- 12VDC Operation
- Through InVid Tech DVR: Free App, CMS & MAC Client

Camera	ELEV-C5DRXIRA27135N
Image Sensor	1/2.7" CMOS Sensor
Signal System	NTSC/PAL
Effective Pixels	2592(H) x 1944(V)
Electronic Shutter	AUTO/ 1/50 (1/60)-1/50,000sec
Min. Illumination	0.01Lux
Video Frame Rate	PAL/NTSC: 5MP@25/30fps
Video Output	"TVI:5MP@20/12.5FPS,4MP@30/25FPS AHD:5MP@20/12.5FPS,4MP@30/25FPS CVI:4MP@30/25FPS CVBS"
Video Output Default	TVI:5MP@20FPS
Camera Features	
S/N Ratio	>41
Noise Reduction	2D&3D DNR
Day&Night	Color / B&W/ AUTO / EXT
White Balance	Auto / Manual/
OSD Language	English / Chinese
AGC	Auto
Mirror Image	Yes
Sharpness	Yes
Defogging	NO
BLC	Yes
DWDR	Yes
Smart IR	Yes
IR LED	30pcs SMD LED
IR Range	98ft (30m)
Lens	
Focal Length	2.7-13.5mm Varifocal Motorised Zoom Lens
Angle of View	"Horizontal FOV: 31.3°-95.8° Vertical FOV: 23.8°-69.1°"
Lens Type	Fixed Iris
Mount Type	Φ14
General	
IP Rating	IP66
Vandalproof	IK10
Power Supply	DC12V
Power Consumption	<6W
Working Temperature / Humidity	-40°F ~ 140°F (-40°C ~ 60°C) RH95% MAX
Dimensions(W×D×H)	.22 x .19 in (5.56"x4.72"mm)
Weight	2.56lbs (1160g)

Ordering Information

ELEV-C5DRXIRA27135N: 5 Megapixel Dome, 2.7-13.5 mm