



ELEVI-P5LIR

5 Megapixel IP Plug & Play, Outdoor Low Profile, 32' IR Range, WDR, Built-in Mic, SD Card Slot, PoE/DC12V

Features

- 5 Megapixel Resolution
- Fixed Lens
- True Day/Night with IR Range up to 32'
- True WDR 120dB
- H.265/H.265+/H.264/H.264+
- Smart Analytics
- TF Card Local Storage: Up to 128GB
- Built-in Mic
- IP66 Weather Resistant
- IK10 Vandal Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps
- Free CMS
- Free MAC client

| | |
|-------------------------|---|
| Model | ELEVI-P5LIR |
| Sensor+DSP | IMX335+Hi3516EV300 |
| Sensor | 1/2.8" Progressive scan CMOS Sensor |
| Min. Illumination | 0.01lux(Color), 0lux(IR on) |
| Lens | 2.8 mm@F1.85: horizontal FOV: 99°, vertical FOV:56° |
| Lens Mount | M12 |
| IR | 14milX18pcs SMD LED |
| IR Range | 98ft (30m) |
| Smart IR | Support |
| Shutter Time | Auto/Manual, 1/3~1/10000s |
| Day/Night | IR cut filter with auto switch |
| Wide Dynamic Range | WDR&DWDR (13fps) |
| Digital noise reduction | 2D/3D DNR |
| Compression Standard | |
| Video Compression | H.264/H.265 |
| H.264 Codec profile | Base/Main/High profile |
| H.265 Codec profile | Main profile |
| Image | |
| Max. Image Resolution | 5MP(2592 x 1944)(default 15fps) |
| Frame Rate | "50Hz: 15fps 5MP (2592 x 1944) 15fps 4MP (2560 x 1440), 15fps 4MP(2304 x 1728) 25fps 3MP(2048 x 1536), 25fps 1080P(1920 x 1080) 25fps 960P (1280 x 960), 60Hz: 15fps 5MP (2592 x 1944) 15fps 4MP (2560 x 1440), 15fps 4MP(2304 x 1728) 30fps 3MP (2048 x 1536), 30fps 1080P(1920 x 1080) 30fps 960P (1280 x 960), 30fps 720P(1280 x 720)" |
| Sub Stream | "50Hz: 25fps 720P(1280 x 720) 25fps D1(704 x 576), 25fps CIF(352 x 288) 60Hz: 30fps 720P(1280 x 720) 30fps D1(704 x 480), 30fps CIF(352 x 240)" |
| Third Stream | N/A |
| Image Setting | Brightness/Contrast/Saturation/Hue/Sharpness |
| BLC | Support |
| HLC | Support |
| ROI | Support |
| Defog | Support |
| Network | |
| Network Storage | N/A |
| Protocols | "TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour, IPv6" |
| Event | Motion Detection, Video Shelter |
| Smart Functions | Line Crossing, Area Intrusion, Region Entrance, Region Exiting, -Fast Moving, Face Detection |
| System compatibility | Onvif (Profile S), CGI |
| Security | User authentication, IP address filtering, Video mask |
| Mobile Surveillance | iPhone, iPad, Android, CMS, WEB |
| Interface | |
| Communication interface | 1 RJ45 10M / 100M/ Ethernet Port |
| General | |
| Operating Conditions | -22°F ~ 140°F (-30°C ~ 60°C) Humidity 95% or less (non-condensing) " |
| Power Supply | DC12V ± 10% |
| POE Supply | PoE (802.3af) |
| Power Consumption | MAX. 8.5W |
| Weather Proof | IP66 |
| Dimensions | 2.65 x 2.26 x 5.98 inches (67.5X57.5X152mm) |
| Weight | 0.80lb (365g) |

Ordering Information

ELEVI-P5LIR: 5 Megapixel IP Plug & Play, Fixed Lens

Made in Indonesia

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.