



## ELEVI-P8BXIRA27135

8 Megapixel IP Plug & Play, Vandal Outdoor Bullet, 165' IR Range, WDR, Built-in Mic, SD Card Slot, PoE/DC12V

### Features

- 8 Megapixel Resolution
- Motorized Auto-Focus 2.7-13.5mm Lens
- True Day/Night with IR Range up to 165'
- H.265/H.265+/H.264/H.264+
- True WDR 120dB
- Smart Analytics
- TF Card Local Storage: Up to 128GB
- Built-in Mic
- IP66 Weather Resistant
- 12VDC/PoE Operation
- Free iOS & Android Apps
- Free CMS
- Free MAC Client

Elevate Model	ELEVI-P8BXIRA27135
Sensor+DSP	IMX415+Hi3516AV200
Sensor	1/2.8" Progressive scan CMOS Sensor
Min. Illumination	0.01Lux(COLOR), 0Lux(IR ON)
Lens	2.7~13.5mm@F1.3;horizontal FOV:109~29° ,vertical FOV:57~16° Motorized Lens
Lens Mount	14
IR	14milX30pcs SMD LED
IR Range	165ft (50m)
Smart IR	Support
Shutter Time	Auto/Manual, 1/3~1/10000s
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	WDR&DWDR
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.264+/H.265/H.265+
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps~10 Mbps
Triple Streams	Support
Audio Compression	G.711A, G.711U
Audio Bit Rate	64 Kbps
Image	
Max. Image Resolution	8MP(3840 × 2160)(default 15fps)
Frame Rate	*50Hz: 15fps 8MP(3840 × 2160), 25fps 5MP(2592 × 1944) 25fps 4MP(2560 × 1440), 25fps 4MP(2304 × 1728) 25fps 3MP(2048 × 1536), 25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960), 60Hz: 15fps 8MP(3840 × 2160), 30fps 5MP(2592 × 1944) 30fps 4MP(2560 × 1440), 30fps 4MP(2304 × 1728) 30fps 3MP(2048 × 1536), 30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960), 30fps 720P(1280 × 720)*
Sub Stream	*50Hz: 25fps 720P(1280 × 720) 25fps D1(704 × 576), 25fps CIF(352 × 288) 60Hz: 30fps 720P(1280 × 720) 30fps D1(704 × 480), 30fps CIF(352 × 240)*
	*50Hz: 25fps CIF(352 × 288) 60Hz: 30fps CIF(352 × 240)*
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Network Storage	NAS(NFS/CIFS)
Protocols	*TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTSP,RTSP,RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour*
Event	Motion Detection, Video Shelter
Smart Functions	"Line Crossing, Area Intrusion, Unattended Object, Object Missing, Region Entrance, Region Exiting, Fast Moving, Loitering Detection, People Gathering Detection, Parking Detection, Blurred Detection, Scene Change Detection, Audio exception Detection, Crossing Line Statistics, Human Body Detection"
System compatibility	CGI
Security	User authentication, IP address filtering, Video mask
Mobile Surveillance	iPhone, iPad, Android devices
Interface	
Communication interface	1 RJ45 10M / 100M Ethernet Port
Storage	Built-in Micro SD/SDHC/SDXC slot, up to 128GB
MIC	Support
General	
Operating Conditions	-22°F ~ 140°F (-30°C ~ 60°C) Humidity 95% or less (non-condensing) "
Power Supply	DC12V ± 10%
POE Supply	PoE (802.3af)
Power Consumption	MAX. 9W
Weather Proof	IP66
Dimensions	9.28 x 3.26 x 2.87 In (235.7*82.9*72.9 mm)
Weight	1.67lb (760g)
POE Supply	PoE (802.3af)
Power Consumption	MAX. 11W
Weather Proof	IP66
Dimensions	ø3.15" x 10.86"
Weight	2.62 lbs (1188g)

### Ordering Information

**ELEVI-P8BXIRA27135:** 8 Megapixel A/F 2.7-13.5mm Lens