



## IMHD-32HDLOOP

32" Full HD 1920 x 1080 LED Monitor, HDMI, VGA, BNC Composite Inputs, BNC HD (TVI/AHD/CVI/CVBS), Audio

- Suitable for every Video Surveillance and Security application: displays HDMI digital plus VGA and BNC analog inputs (with Looping BNC analog output)
- Fully tested, approved and licensed by the HDMI Forum to bear the official HDMI logo
- Support 3D comb filter and 3D de-interlace, High quality image
- Auto-on when VGA or HDMI DVR/NVR video is detected
- Bright LED illuminated panel with wide viewing angle
- Built in stereo 8Ω x 2W speakers and audio amplifier
- Included desk stand is easily removable for standard VESA mounting
- The accessories include VGA line and power line
- Support TVI & AHD & CVI 1080P camera display
- CE, FCC certificates included

Model	IMHD-32HDLOOP
Screen diagonal dimension	31.5 inch
View able area W x H	698.40x392.85
Led Type	LED
Pixel Pitch	0.36*0.36mm
Screen Maximum Resolution	1920x1080
Supported input Resolutions	720x400;640x480;800x600;1024x768;1280x1024;1920x1080
Refresh Rate(vertical Frequency)	60,70, 75 Hz depending on resolution
Color Depth	24 bits;16.7 Million colors
Brightness	300 cd/m <sup>2</sup>
Auto Adjust	Yes
Monitor Aspect Ratio	0.672916667
Display Aspect Ratio	OSD selectable 16:9 or 4:3
Horizontal TV Lines	1080
Contrast Ratio	125.0006944
Response Time(ms)	6.5
View Angle H/V	178°/178°
Digital Video Inputs	HDMI up to 1920x1080
Port inputs	HDMI+VGA+ BNC IN+Audio in+ HD IN (TVI AHD CVI CVBS)+USB(update)
Port outputs	HD OUT (TVI AHD CVI CVBS)
Speakers	8 Ω 2 Watt/channel
Filter type	3D Comb filter
De-interlace & Noise Reduction	3D De-interlace
OSD Languages	English, Spanish, German, Chinese, French, Italian
Monitor Body Dimensions (W x L x D)	29.3 x 17.5 x 2.3 In (743.95x443.40x58.70mm)
Max Dimensions Monitor + Wall Mount (mm)	29.3 x 20.6 x 7.8 In (743.95x523.70x199.30mm)
Case & stand material	Plastic
VESA Mounting Pattern	200mmx100mm; location centered on monitor body
Net weight	19.4 lbs (8.8kg)
Gross weight	23.8 lbs (10.8kg)
Power- Watts(on and standby)	<55W
Power input	100 ~ 240V AC
Operating Temperature	32° ~ 104°F (0°C ~ 40°C)
Storage Temperature	-4° ~ 140°F (-20°C ~ 60°C)
Operating Humidity	10 ~ 85%
Certifications	CE,FCC,HDMI Forum

### Ordering Information

**IMHD-32HDLOOP:** 32" HDMI Monitor

*InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.*