



VIS-P5BXIR28NH

5 Megapixel IP Plug & Play, Outdoor Bullet, 131' EXIR Range, WDR, Built-in Mic, SD Card Slot, PoE/12VDC

Features

- True AI Human and Vehicle Classification for Line Crossing and Intrusion Detection
- 5 Megapixel Resolution
- Fixed Lens
- True Day/Night with IR Range up to 98-164'
- Smart IRs
- Starlight Illumination
- Ultra H.265/H.265/H.264/MJPEG Compression
- 25 FPS Recording and Live
- WDR
- Smart Analytics
- Micro SD Slot: Up to 256GB
- Built-in Mic
- IP67 Weatherproof
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

Camera	VIS-P5BXIR28NH				
Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F1.6 4.0mm@F1.6				
DORI Distance	Lens (mm)	Detect(ft)	Observe(ft)	Recognize(ft)	Identify(ft)
	2.8	206.7(63m)	82.7(25.2m)	41.3(12.6m)	20.7(6.3m)
Angle of View (H)	4.0	295.3(90m)	118.1(36m)	59.1(18m)	29.5(9m)
	112.7°	86.5°			
Angle of View (V)	60.1°	44.1°			
Angle of View (O)	146.5°	112.5°			
Shutter	Auto/Manual, 1 ~ 1/100000s				
Adjustment angle	Pan: 0°~360°		Tilt: 0° ~ 90°		Rotate: 0°~360°
Min. Illumination	0Lux with IR on				
Digital noise reduction	2D/3D DNR				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>56dB				
IR Range	131 ft (Up to 40m) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				

WDR	120dB
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile
Frame Rate	Main Stream:5MP (2880*1620), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 25fps; 1080P (1920*1080), Max 30fps; Sub Stream: D1 (720*576), Max 30fps; Third Stream: CIF (352*288), Max 30fps
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal
Dewarping	Supported
HLC	Supported
BLC	Supported
Audio	
Audio Compression	G.711
Suppression	Supported
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
Smart	
Behavior Detection	Line crossing detection, Intrusion detection, Region entrance detection, Region exit detection ;Motion detection, Tampering alarm, Audio Detection
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Clients	InVid Vision (Mobile App) Vision Tools (IP Utility) InVid CMS
Web Browser	Plug-in required live view: IE9+, Chrome 41& below, Firefox 52 & below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Network	1 RJ45 10M/100M Base-TX Ethernet
Built-in Mic	Supported
Certifications	
Certifications	CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 6.4W
Dimensions (L x W x H)	6.1" x 2.5" x 2.5" (155.9 x 63.1 x 62.7mm)
Net Weight	0.99lb (0.45kg)
Material	Metal
Working Environment	-22°F ~ 140°F (-30°C ~ 60°C), Humidity: ≤95% RH (non-condensing)
Storage Environment	-22°F ~ 140°F (-30°C ~ 60°C), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Ingress Protection	IP67

Ordering Information

VIS-P5BXIR28NH: 5 Megapixel IP Plug & Play Outdoor Bullet