



VIS-LRPOE16-2

16-Port PoE Switch with 2x Gigabit Combo Port

Features

- 16x10/100Mbps Ethernet Ports
- 2xGigabit combo port (RJ45 & SFP)
- All 100Mbps ports support PoE
- PoE complies with IEEE802.3af/at, up to 30W for single port
- Up to 820 foot transmission distance on EXTEND mode
- Easy-to-use, no need to configure
- High quality with all metal housing

Model	VIS-LRPOE16-2
Ports	16x10/100Base-TX autosensing Ethernet ports (all support PoE) 2xGigabit combo port (RJ45 and SFP)
Port attribute	10/100/1000Mbit/s transfer rate Half-duplex, full-duplex and auto-negotiation Auto MDI/MDIX
Standards	IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T IEEE 802.3z 1000BASE-X ANSI/IEEE 802.3 NWay IEEE 802.3x flow control IEEE 802.3af PoE IEEE 802.3at PoE
MAC	4K
Packet forwarding rate	6.55Mpps
Switching capacity	8.8Gbps
Jumbo Frames	Support
EXTEND mode	Disabled: all ports can communicate with each other, and monitoring optimization is disabled. Enabled: Downlink ports can only communicate with uplink ports, monitoring optimization is enabled, and transmission distance can be extended to up to 820 Feet.
Status LEDs	Link/Act (steady green): link is normal Link/Act (flashing green): data is being forwarded Link/Act (off): no link PoE (steady orange): the port is powering a powered device properly PoE (off): the port is not connected to any powered device or is not supplying power
PoE	802.3at/af Max PoE capacity: 250 W
Consumption	≤ 300 W
AC voltage	100-240 V
Operating temperature	32°F-104°F (0°C-40°C)
Operating humidity	10%-85%
Storage temperature	14°F-158°F (-10°C-70°C)
Storage humidity	10%-90%
Dimensions (WxD×H)	17.3 x 11 x 1.7" (440 x 280 x 44mm)

Ordering Information

VIS-LRPOE16-2: 16-Port PoE Switch with 2x Gigabit Combo Port