



### VIS-P4TXIR28NH

4 Megapixel IP Plug & Play, Outdoor Turret  
Fixed Lens, up to 98' IR Range, WDR, SD Card Slot, PoE/DC12V

#### Features

- Smart Analytics-AI Human Body Detection
- 4 Megapixel Resolution
- Fixed Lens
- True Day/Night with
- IR Range up to 98'
- Smart IRs
- Ultra H.265/H.265/H.264/
- MJPEG Compression
- 30 FPS Recording and Live
- True WDR 120dB
- Cloud Upgradeable
- Micro SD Slot: Up to 256GB
- IP67 Weatherproof
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

Camera	VIS-P4TXIRNH			
Sensor	1/3", 4.0 megapixel, progressive scan, CMOS			
Lens	2.8mm@F2.0			
DORI Distance	Lens (mm)	Detect (ft)	Observe (ft)	Recognize (ft) Identify (ft)
	2.8	206.7(63m)	82.7(25.2m)	41.3(12.6m) 20.7(6.3m)
Angle of view(H)	107.8°			
Angle of View (V)	57.0°			
Angle of View (O)	140.1°			
Adjustment angle	Pan: 0° ~ 360° Tilt: 0° ~ 80° Rotate: 0° ~ 360°			
Shutter	Auto/Manual, 1 ~ 1/100000s			
Minimum Illumination	Colour:0.01Lux (F2.0, AGC ON)			
	0Lux with IR on			
Day/Night	IR-cut filter with auto switch (ICR)			
Digital noise reduction	2D/3D DNR			
S/N	>56dB			
IR Range	Up to 98ft (30m) IR range			
Wavelength	850nm			
IR On/Off Control	Auto/Manual			
Defog	Digital Defog			
WDR	120dB			

Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile
Frame Rate	Main Stream: 4MP (2688*1520), Max 30fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps; 1080P(1920*1080),Max30fps
	Sub Stream: 720P (1280*720), Max 30fps;
	Third Stream: 4CIF (704*576), Max 30fps
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 4 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°
Dewarping	NA
HLC	Supported
BLC	Supported
Audio	
Audio Compression	G.711
Suppression	Supported
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
Smart	
Behavior Detection	Intrusion, Human Body Detection, Motion detection, Tampering alarm, Audio Detection
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Clients	InVid Vision (Mobile App)
	Vision Tools (IP Utility)
	InVid CMS
Web Browser	Plug-in required live view: IE9+, Chrome 41 & below, Firefox 52& below
	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Network	1 RJ45 10M/100M Base-TX Ethernet
Built-in Mic	Supported
Certifications	
Certifications	CE: EN 60950-1
	UL: UL60950-1
	FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 5.5W
Dimensions (Ø x H)	Φ4.6" x 3.8" (Φ118 x 96mm)
Net Weight	0.73lb (0.33kg)
Material	Metal + Plastic
Operating Conditions	-22°F ~ 140°F (-30°C ~ 60°C), Humidity: ≤95% RH (non-condensing)
Storage Environment	-22°F ~ 140°F (-30°C ~ 60°C), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Ingress Protection	IP67

#### Ordering Information

**VIS-P4TXIR28NH:** 4 Megapixel IP Plug & Play, Outdoor Turret, 2.8mm

*InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.*