



## VIS-P5DRXIRA27135NH

5 Megapixel IP Plug & Play, Outdoor Dome, 2.7-13.5mm Auto-Focus Motorized, 131' IR Range, WDR, Audio Input/Output, Built-in Mic, SD Card Slot, PoE/DC12V

### Features

- True AI Human and Vehicle Classification for Line Crossing and Intrusion Detection
- 5 Megapixel Resolution
- Motorized Auto-Focus 2.7-13.5mm Lens
- True Day/Night with IR Range up to 131'
- Smart IRs
- Starlight Illumination
- Ultra 265/H.264/MJPEG
- 25 FPS Recording & Live
- True WDR 120dB
- Cloud Upgradeable
- Micro SD Slot: Up to 256GB
- Audio Input: Built-in Mic
- Audio Output
- IP67 Weatherproof
- IK10 Vandal Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Vison CMS
- Free MAC Client
- NDAA Compliant

Camera	VIS-P5DRXIRA27135NH			
Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS			
Lens	2.7 ~ 13.5mm, AF automatic focusing and motorized zoom lens			
DORI Distance	Lens (mm)	Detect (ft)	Observe (ft)	Recognize (ft)
	Identify (ft)			
DORI Distance	2.7	199.5(60.8m)	79.7(24.3m)	40(12.2m)
	13.5	996.7(303.8m)	398.6(121.5m)	199.5(60.8m)
Angle of View (H)	106.25°~ 30.42°			
Angle of View (V)	56.36°~ 17.22°			
Angle of View (O)	110.34°~ 34.18°			
Adjustment angle	Pan: 0° ~ 355°	Tilt: 0° ~ 80°	Rotate: 0° ~ 355°	
Shutter	Auto/Manual, 1 ~ 1/100000s			
Minimum Illumination	Colour:0.002 Lux (F1.35, AGC ON) 0Lux with IR			
Day/Night	IR-cut filter with auto switch (ICR)			
Digital noise reduction	2D/3D DNR			
S/N	>56dB			
IR Range	Up to 131ft (40m) IR range			
Wavelength	850nm			

IR On/Off Control	Auto/Manual
Defog	Digital Defog
WDR	120dB
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile
Frame Rate	Main Stream:5MP (2880*1620), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 25fps; 1080P (1920*1080), Max 30fps; Sub Stream: D1 (720*576), Max 30fps; Third Stream: CIF (352*288), Max 30fps
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise
Dewarping	Supported
HLC	Supported
BLC	Supported
Audio	
Audio Compression	G.711
Two-way audio	Supported
Suppression	Supported
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR
Smart	
Behavior Detection	Line crossing detection, Intrusion detection, Region entrance detection, Region exit detection ;Motion detection, Tampering alarm, Audio Detection
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Client	Vision CMS, InVid Vision
Web Browser	Plug-in required live view: IE9+, Chrome 41 & below, Firefox 52 & below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Audio I/O	Input: impedance 35kΩ; amplitude 2V [p-p] Output: impedance 600Ω; amplitude 2V [p-p]
Alarm I/O	1/1
Built-in Mic	Supported
Audio Sensitivity	-32±3dB
Network	1 RJ45 10M/100M Base-TX Ethernet
Certifications	
Certifications	CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 5.5W
Dimensions (Ø x H)	Φ 5.8" x 4.4" (148 x 111mm)
Net Weight	0.99lb (0.45kg)
Material	Metal + Plastic
Working Environment	-22°F ~ 140°F (-30°C ~ 60°C), Humidity: ≤95% RH (non-condensing)
Storage Environment	-22°F ~ 140°F (-30°C ~ 60°C), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Reset Button	Supported
Ingress Protection	IP67
Vandal Resistant	IK10

### Ordering Information

**VIS-P5DRXIRA27135NH:** 5 Megapixel IP Plug & Play Outdoor Dome 2.7-13.5mm A/F Motorized

**VIS-P5DRXIRA27135NH-B:** 5 Megapixel IP Plug & Play Outdoor Dome 2.7-13.5mm A/F Motorized, Black Housing

*InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.*