



VIS-P8PTZXIRA22XPOE

8 Megapixel Outdoor PTZ, Motorized Auto-Focus 6.5-143mm Lens, IR Range up to 656', Audio Input/Output, 24VAC/PoE++ Operation

- 8 Megapixel Resolution
- Motorized Auto-Focus 6.5-143mm Lens
- IR Range up to 656'
- Ultra H.265/H.265/H.264/MJPEG Compression
- 30 FPS Recording and Live
- True WDR 120dB
- Micro SD Slot: Up to 256GB
- Audio Input
- Audio Output
- IP67 Weatherproof
- IK10 Vandal Resistant
- 24VAC/PoE++ Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

Camera	VIS-P8PTZXIRA22XPOE															
Sensor	1/1.8", progressive scan, 8megapixel, CMOS															
Lens	6.5~ 143 mm (22x optical zoom) , AF automatic focusing & motorized zoom lens															
DORI Distance	<table border="1"> <thead> <tr> <th>Lens</th> <th>Detect(ft)</th> <th>Observe(ft)</th> <th>Recognize(ft)</th> <th>Identify(ft)</th> </tr> </thead> <tbody> <tr> <td>6.5mm</td> <td>480(146.3m)</td> <td>191.9 (58.5m)</td> <td>96.1 (29.3m)</td> <td>47.9(14.6m)</td> </tr> <tr> <td>143mm</td> <td>10556(3217.5m)</td> <td>4222.4(1287m)</td> <td>2111.2(643.5m)</td> <td>1055.8(321.8m)</td> </tr> </tbody> </table>	Lens	Detect(ft)	Observe(ft)	Recognize(ft)	Identify(ft)	6.5mm	480(146.3m)	191.9 (58.5m)	96.1 (29.3m)	47.9(14.6m)	143mm	10556(3217.5m)	4222.4(1287m)	2111.2(643.5m)	1055.8(321.8m)
	Lens	Detect(ft)	Observe(ft)	Recognize(ft)	Identify(ft)											
6.5mm	480(146.3m)	191.9 (58.5m)	96.1 (29.3m)	47.9(14.6m)												
143mm	10556(3217.5m)	4222.4(1287m)	2111.2(643.5m)	1055.8(321.8m)												
Angle of View (H)	58.9°~3.4°															
Angle of View (V)	35.2°~1.9°															
Angle of View (O)	72.5°~4.1°															
Shutter	Auto/Manual, shutter time: 1 ~ 1/1000000 s															
Minimum Illumination	Colour: 0.003 lux (F1.5,AGC ON) 0 lux with IR															
Iris	Auto/Manual, F1.5 ~ F3.4															
Day/Night	IR-cut filter with auto switch (ICR)															
Digital noise reduction	2D/3D DNR															
S/N	>56 dB															
IR Range	UP to 656ft (200m)															
Defog	Digital Defog															
WDR	120dB															
Video																
Video Compression	Ultra 265,H.265, H.264, MJPEG															
H.264 code profile	Baseline profile, Main Profile, High Profile															
Frame Rate	Main Stream:8MP(3840 × 2160): Max.30fps, 2MP(1920×1080)@30fps, Sub Stream:2MP(1920×1080) : Max. 30fps, Third Stream: D1 (720×576): Max. 30fps															
HLC	Supported															
BLC	Supported															
EIS	Supported															
OSD	Up to 8 OSDs															
Privacy Mask	Up to 24 areas															
ROI	Up to 8 areas															
Motion Detection	Up to 4 areas															
Smart																
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication															
Audio																
Audio Compression	G.711															
Two-way Audio	Supported															
Suppression	Supported															
Sampling Rate	8 KHZ															
Storage																
Edge Storage	Micro SD, up to 256 GB															
Network Storage	ANR															
Network																
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS															
Compatible Integration	ONVIF(Profile S, Profile G, Profile T),API															
Pan & Tilt																
Pan Range	360°															
Pan Speed	0.1°/s ~ 200°/s Preset speed: 300°/s															
Tilt Range	-15° ~ +90° (auto reverse)															
Tilt Speed	0.1° ~200°/s Preset speed: 240°/s															
Number of Presets	1024															
Patrol	Preset patrol, route patrol, recorded patrol															
Home Position	Supported															
Interface																
Audio I/O	Audio cable 1 Input: impedance 35 kΩ; amplitude 2 V *p-p] 1 Output: impedance 600 Ω; amplitude 2 V *p-p]															
Alarm I/O	1/1															
Network	1 RJ45 10M/100M Base-TX Ethernet															
General																
Power	24 V AC±25%, 24 V DC±25%, PoE++ (PSE Required) Power consumption: 60W															
Dimensions (Ø x H)	Ø8.9" x 14.2" (Ø227x359.4 mm)															
Weight	12.24 lb (5.55 kg)															
Working Environment	-40°F ~ 158°F (-40°C ~ +70°C), Humidity: ≤95% RH(non-condensing)															
Reset Button	Supported															
Ingress Protection	IP66															
Certification	UL															

Ordering Information

VIS-P8PTZXIRA22XPOE: 8 Megapixel Resolution, Motorized Auto-Focus 6.5-143mm Lens